CashAccSys Grande



With G+D BVM Deposit Device
Datasheet



The CashAccSys Grande is a secure on-line cash-receiving terminal.

The CashAccSys Grande has a bag capacity of up to 20 000 notes and is available as a SABS categorised safe. Integrated with the new OEM Giesecke + Devrient BVM 120 note counter. The CashAccSys Grande is perfectly suited to the African and Asian market where note value is low or international markets where multiple currencies are handled as well as high cash volume clients. The CashAccSys Grande can count and validate up to five currencies simultaneously providing complete cash 360 overview for retailers, banks, exchange companies and duty free.

Key Features

- Secure cash receiving terminal
- Easy reconciling of cash takings
- 10" touch screen XML ready
- High speed note counter, with high acceptance rate
- Full counterfeit validation with 93 currencies recognised
- Low Jam rate
- Detailed receipt print-out
- Anti-Tamper bag design



General Specifications

Physical security	Propriety Graded Safe with CAT 3 and CAT 4 options
Power supply	220 volt AC
Environment	Ambient +10 C° to +45 C°
Installation	Indoor Only
Communication protocol	Windows System, TCP/IP with XML Ready interface
Interfaces with POS system	Compatible Windows POS systems, or integration into Android applications
Comprehensive audit trail	Yes
Integrated back end solution	C-Online cloud-based reporting
Biometric	Optional
Locks	Dual Keys or Bluetooth Reky Lock
Electronic lock on all doors	Optional
Battery back up	Optional
Touch screen	10.2 inch colour touch panel
Card reader	Optional
Barcode reader	Optional
Multi-currency	Yes

CashAccSys Grande Specifications

Processing Speed	800 banknotes/ minute
Hopper Capacity	300 banknotes
Reject Stacker Capacity	50 banknotes
Bag Note Capacity	10 000 – 15 000 notes
Printer	Thermal Custom Plus II 58mm(w) x 50mm(h)
Denomination detection	Full CIS, 100 DPI, IR, transmissive & reflective, UV, MT, MG
Banknote insertion	Banknotes are recognised, irrespective of their orientation, face up or down
Dimensions (HxWxD), with weight dependant on safe rating	112 x 56 x 62cm
Counterfeit detection	Yes
Connectivity	RS232 and LAN